



LP1366

TURNBUCKLES

Material

Steel (1.0037 up to M36, above M36 1.0052).

Hot dip galvanized version, available on request providing increased protection

against corrosion. Please add -FZ for hot dip galvanized, e.g. LP1366.R006-FZ.

Technical Notes

To DIN 34828.

Important Notes

Turnbuckles are not to be used for lifting. Only suitable for use in tension.

Order No.	Thread hand	d	l_1	l_2	S.W.L. kg	Weight kg
LP1366.R006	Right	M 6	120	60	0.02	0.02
LP1366.R008	Right	M 8	120	65	0.04	0.04
LP1366.R010	Right	M10	150	75	0.07	0.07
LP1366.R012	Right	M12	150	75	0.11	0.11
LP1366.R014	Right	M14	165	80	0.15	0.15
LP1366.R016	Right	M16	200	100	0.26	0.26
LP1366.R020	Right	M20	200	120	0.44	0.44
LP1366.R024	Right	M24	260	150	0.76	0.76
LP1366.R030	Right	M30	260	160	1.20	1.20
LP1366.R036	Right	M36	300	180	2.10	2.10
LP1366.R042	Right	M42	350	200	3.15	3.15
LP1366.R048	Right	M48	380	220	4.60	4.60
LP1366.R056	Right	M56	380	230	6.28	6.28
LP1366.R064	Right	M64	425	300	9.16	9.16
LP1366.R072	Right	M72	400	270	4.60	4.60
LP1366.L006	Left	M 6	120	60	0.02	0.02
LP1366.L008	Left	M 8	120	65	0.04	0.04
LP1366.L010	Left	M10	150	75	0.07	0.07
LP1366.L012	Left	M12	150	75	0.11	0.11
LP1366.L014	Left	M14	165	80	0.15	0.15
LP1366.L016	Left	M16	200	100	0.26	0.26
LP1366.L020	Left	M20	200	120	0.44	0.44
LP1366.L024	Left	M24	260	150	0.76	0.76
LP1366.L030	Left	M30	260	160	1.20	1.20
LP1366.L036	Left	M36	300	180	2.10	2.10
LP1366.L042	Left	M42	350	200	3.15	3.15
LP1366.L048	Left	M48	380	220	4.60	4.60
LP1366.L056	Left	M56	380	230	6.28	6.28
LP1366.L064	Left	M64	425	300	9.16	9.16
LP1366.L072	Left	M72	400	270	4.60	4.60